## WHAT IS CLAIMED IS:

- 1. An anti-glare hard coat film comprising a transparent substrate film and an anti-glare hard coat layer disposed at least on one face of the transparent substrate film, wherein the anti-glare hard coat layer comprises (A) a resin cured by an ionizing radiation and, per 100 parts by weight of the cured resin, 0.2 to 10 parts by weight of (B) fine particles of silica and 1 to 20 parts by weight of (C) fine particles of a silicone resin.
- 2. An anti-glare hard coat film according to Claim 1, wherein the fine particles of a silicone resin of component (C) in the anti-glare hard coat layer are fine particles of polyorganosilsesquioxane having a crosslinked structure forming a three-dimensional network.
- 3. An anti-glare hard coat film according to Claim 1, wherein, in the anti-glare hard coat layer, an average diameter (d<sub>B</sub>) of the fine particles of silica of component (B) is in a range of 0.1 to 5 μm, an average diameter (d<sub>C</sub>) of the fine particles of a silicone resin of component (C) is in a range of 0.1 to 3 μm, and a ratio of d<sub>C</sub> to d<sub>B</sub> (d<sub>C</sub>/d<sub>B</sub>) is in a range of 0.5 to 1.

20

5

- 4. An anti-glare hard coat film according to Claim 2, wherein, in the anti-glare hard coat layer, an average diameter (d<sub>B</sub>) of the fine particles of silica of component (B) is in a range of 0.1 to 5  $\mu$ m, an average diameter (d<sub>C</sub>) of the fine particles of a silicone resin of component (C) is in a range of
- 25 0.1 to 3  $\mu$ m, and a ratio of d<sub>C</sub> to d<sub>B</sub> (d<sub>C</sub>/d<sub>B</sub>) is in a range of 0.5 to 1.

- 5. An anti-glare hard coat film according to Claim 1, wherein a thickness of the anti-glare hard coat layer is in a range 0.5 to  $20~\mu m$ .
- 6. An anti-glare hard coat film according to Claim 2, wherein a thickness
  of the anti-glare hard coat layer is in a range 0.5 to 20 μm.
  - 7. An anti-glare hard coat film according to Claim 3, wherein a thickness of the anti-glare hard coat layer is in a range 0.5 to 20  $\mu m$ .
- 10 8. An anti-glare hard coat film according to Claim 4, wherein a thickness of the anti-glare hard coat layer is in a range 0.5 to 20  $\mu m$ .